

REINVENTING THE WORKSTATION FOR AI **NVIDIA QUADRO GV100**

OUFOR

The Power To Accelerate AI-**Enhanced Workflows**

The NVIDIA® Quadro® GV100 reinvents the workstation to meet the demands of Al-enhanced design and visualization workflows. It's powered by NVDIA Volta, delivering extreme memory capacity, scalability, and performance that designers, architects, and scientists need to create, build, and solve the impossible.

Supercharge Rendering with AI

- > Work with full fidelity, massive datasets
- Enjoy fluid visual interactivity with AI-accelerated > denoising

Bring Optimal Designs to Market Faster

Work with higher fidelity CAE simulation models Explore more design options with faster solver > performance

Enjoy Ultimate Immersive Experiences

- Work with complex, photoreal datasets in VR
- Enjoy optimal NVIDIA Holodeck experience

Realize New Opportunities with AI

- Access DL frameworks for AI development via NVIDIA NGC
- Accelerate AI training/inferencing with Tensor Cores and > **NVLink**

All Quadro cards are certified with a broad range of professional applications, tested by leading workstation manufacturers, and backed by a global team of support specialists to give you the peace of mind to focus on doing your best work.

To learn more about the NVIDIA Quadro GV100 visit www.pny.eu/quadro

 1 NVIDIA NVLink sold separately \mid 2 Connecting two GV100 cards with NVLink to scale performance and memory capacity to 64 GB is only possible if your application supports NVLink technology. Please contact your application provider to confirm their support of NVLink. \mid 3 VGA/DVI/HDMI/stereo support via adapter/connector/bracket \mid 4 Quadro Sync II card sold separately \mid 5 Windows 7, 8, 8.1, 10 and Linux \mid 4 Product is based on a published Khronos Specification, and is expected to pass the Khronos Conformance Testing Process when available. Current conformance status can be found at www.khronos.org/conformance \mid 7 GPU supports DX 12.0 API, Hardware Feature Level 12_1

© 2018 NVIDIA Corporation and PNY. All rights reserved. NVIDIA, the NVIDIA logo, Quadro, nView, NVLink, CUDA, GPUDirect, and NVIDIA Volta are trademarks and/ or registered trademarks of NVIDIA Corporation in the U.S. and other countries. The PNV logotype is a registered trademark of PNV Technologies. OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc. All other trademarks and copyrights are the property of their respective owners. MAR18

FEATURES

- > Four DisplayPort 1.4 Connectors³
- > DisplayPort with Audio
- > 3D Stereo Support with
- Stereo Connector³ > NVIDIA GPUDirect[™] Support
- > NVIDIA NVLink Support
- > Quadro Sync II⁴ Compatibility
- > NVIDIA nView[®] Desktop Management Software
- > HDCP 2.2 Support
- > NVIDIA Mosaic⁵

PACKAGE CONTENTS

- > NVIDIA Quadro GV100
- > Quick Start Guide
- > Quadro Support Guide
- > 4 DisplayPort to DVI Adapters
- > 1 DisplayPort to HDMI
- Adapter > 1 Stereo Connector Bracket
- > 1 Auxiliary Power Cable
- (8-pin to dual 6-pin adapter)

WARRANTY AND SUPPORT

- > 3-Year Warranty
- > Pre- and Post-Sales Technical Support
- > Dedicated Field Application Engineers
- > Direct Tech Support Hot Lines



C

PNY PART NUMBER	VCQGV100-PB
SPECIFICATIONS	
GPU Memory	32 GB HBM2
Memory Interface	4096-bit
Memory Bandwidth	Up to 870 GB/s
ECC	Yes
NVIDIA CUDA Cores	5,120
NVIDIA Tensor Cores	640
Double-Precision Performance	7.4 TFLOPS
Single-Precision Performance	14.8 TFLOPS
Tensor Performance	118.5 TFLOPS
NVIDIA NVLink	Connects 2 Quadro GV100 GPUs ²
NVIDIA NVLink bandwidth	200 GB/s
System Interface	PCI Express 3.0 x 16
Max Power Consumption	250 W
Thermal Solution	Active
Form Factor	4.4" H x 10.5" L, Dual Slot, Full Height
Display Connectors	4x DP 1.4
Max Simultaneous Displays	4 direct, DP 1.4
Display Resolution	4x 4096x2160 @ 120 Hz 4x 5120x2880 @ 60 Hz 2x 7680x4320 @ 60 Hz
VR Ready	Yes
Graphics APIs	Shader Model 5.1, OpenGL 4.5 [¢] , DirectX 12.0 ⁷ , Vulkan 1.0 [¢]
Compute APIs	CUDA, DirectCompute, OpenCL™

PNY Technologies Europe



Zac du Phare, 9 Rue Joseph Cugnot BP 40181 33708 Mérignac Cedex | France T +33 (0)5 56 13 75 75 | F +33 (0)5 56 13 75 77